

Wire Protocol

[Return to Glossary](#)

Wire Protocol refers to a way of getting data from [point-to-point](#): A Wire [protocol](#) is needed if more than one application has to interoperate. It generally refers to protocols higher than the [physical layer](#). In contrast to transport protocols at the transport level (like [tcp](#) or [udp](#)), the term “wire protocol” is used to describe a common way to represent information at the Application Level of the [Open Systems Interconnection \(OSI\) Model](#). It refers only to a common [Application Layer](#) protocol and not to a common object semantic[clarification needed] of the applications. Such a representation at application level needs a common [xml_info](#)set and a data binding (using e.g. a common encoding scheme like [xsd](#)).

It generally refers to higher layers, including [Ethernet](#) and ATM (layer 2) and even higher layer distributed object protocols such as SOAP, [CORBA](#) or RMI.

The Wire Protocol may be either text-based or a binary protocol. Although an important architectural decision, this is a separate matter from the distinction between Wire Protocols and programmatic [Application Programming Interfaces \(APIs\)](#).

Source: [Wire Protocol](#)

From:
<https://omgwiki.org/ddsf/> - **DDS Foundation Wiki**

Permanent link:
https://omgwiki.org/ddsf/doku.php?id=ddsf:public:guidebook:06_append:glossary:w:wireprotocol&rev=1626292306

Last update: **2021/07/14 15:51**

