4.1.1.4 Network Platforms

Return to Platforms

A DIDO, by definition, is a collection of networked nodes. Traditionally, the network is assumed to be Ethernet with nodes connected over Local Area Network (LAN) and/or a Wide Area Network (WAN) using a Network Device.

The connections can either be:

- Wired Network using
  - Network Cabling
  - Universal Serial Bus (USB)
2. Wireless Network using Wireless Fidelity (Wi-Fi)

   Note: for Private, permissioned DIDOs, there may be explicit bans on wireless or even USB connections.

   However, there is a lot of growth and development using other wireless connections other than Ethernet or USB. For example:

   - Bluetooth
   - ZigBee
   - Near-Field-Communication (NFC)

   Consequently, it is important to identify the kinds of connections that are required to support the DIDO. Some example are:

   - Many contactless payments systems use Radio Frequency Identification (RFID) and NFC
   - Many supply chains use RFID
   - Many smart home efforts use WiFi and zigbee
   - Many automobiles use Bluetooth to connect phones, make queries, play music, etc.

From:
https://omgwiki.org/dido/ - **DIDO Wiki**

Permanent link:
https://omgwiki.org/dido/doku.php?id=dido:public:ra:1.4_req:1_func:platform:net_arch&rev=1607641912

Last update: **2020/12/10 18:11**