

F.17 Destination Order

[Return to DDS Quality of Service](#)

The DESTINATION_ORDER policy controls how each [subscriber](#) resolves the final value of a data [instance](#) that is written by multiple DataWriter objects (which may be associated with different [Publisher](#) objects) running on different nodes.

The setting BY_RECEPTION_TIMESTAMP indicates that, assuming the [OWNERSHIP](#) policy allows it, the latest received value for the instance should be the one whose value is kept. This is the default value.

The setting BY_SOURCE_TIMESTAMP indicates that, assuming the OWNERSHIP policy allows it, a timestamp placed at the source should be used. This is the only setting that, in the case of concurrent same-[strength](#) DataWriter objects updating the same instance, ensures all subscribers will end up with the same final value for the instance. The mechanism to set the source timestamp is [middleware](#) dependent.

The value offered is considered compatible with the value requested if and only if the inequality offered **kind** >= requested **kind** evaluates to TRUE. For the purposes of this inequality, the values of DESTINATION_ORDER **kind** are considered ordered such that BY_RECEPTION_TIMESTAMP < BY_SOURCE_TIMESTAMP.

Source: [DDS 1.4 Spec](#)

From:
<https://omgwiki.org/dido/> - DIDO Wiki

Permanent link:
https://omgwiki.org/dido/doku.php?id=dido:public:ra:xapend:xapend.f_qos:destination_order&rev=1624571804

Last update: 2021/06/24 17:56

